

# CCS-2300

## Counter Communication System



Commercial Audio introduces CCS-2300, a two-way counter communication system, exclusively designed for easy and effective conversation across counters with transparent security barriers. It consists of an attendant unit, a customer unit and a power supply unit, which are easy to install and simple to connect through dedicated cables as supplied with the system.

### Features:

- ✓ Unique design, pleasing aesthetics & rugged construction.
- ✓ Two-way, hands-free communication.
- ✓ Easy, hassle-free installation.
- ✓ Compact & elegant table top attendant unit with 20" long gooseneck microphone for strain-free usage.
- ✓ A 3.5mm jack socket is provided for connecting a headband microphone like the HBM-50. This is useable by the attendant as an alternate to the fixed gooseneck microphone.
- ✓ Separate controls for adjusting the speech levels during Talk & Listen modes of operation.
- ✓ Special Auto-Mute ON/OFF option provided through a toggle switch.noise. In Auto-Mute ON condition, the customer's microphone is partially muted if it is not used for 30 sec. approx. This facility prevents the attendant from being disturbed by unwanted outside noise
- ✓ The customer's unit has an efficient speaker and a sensitive condenser cartridge, mounted in a beautifully designed housing.
- ✓ Attendant's microphone has voice priority over the customer's microphone.
- ✓ With Effector input and output for EQ, mixer and DSP.
- ✓ With one RS232 communication port for central control system.
- ✓ AUX and AUX output for extra sound amplification equipments.
- ✓ Bass, treble, MIC, AUX, Monitor and Master volume control.
- ✓ Included with one 13 meters cable with 8 PIN plug.

**Specification:**

<b>Model</b>	<b>CCS-2300</b>
<b>Description</b>	<b>Counter Communication System</b>
<b>Output</b>	2W (Max.) in each amplifier
<b>Microphone Element</b>	Electret Condenser in both the units.
<b>Auto Mute `ON`</b>	Enables after 30 seconds (approx.)
<b>Power Requirement</b>	AC: 220-240V, 50/60Hz
<b>Protections</b>	AC Fuse 1 × 0.5A
<b>Dimensions</b>	
<b>Attendant Unit</b>	W116 x H65 x D170 mm (w/o gooseneck)
<b>Customer Unit</b>	∅98 x D52mm
<b>Power Supply Unit</b>	W85 × H58 × D150 mm
<b>Weight</b>	
<b>Attendant Unit</b>	1.3kg
<b>Customer Unit</b>	0.55kg
<b>Power Supply Unit</b>	0.93kg
<b>Accessories</b>	1 No. of fuse 0.5A, 2 Nos. of M4 moulded screws, 2 Nos. of self adhesive
	DUAL LOCK tape, 4.5mtrs. of interconnecting cable for Customer unit