



Wireless A2R (ROR) Heat Detector

✓ Key Features



EN54-25 approved



868 - 870 MHz operating frequency



Powered by lithium metal batteries



Modern design



360 degree LED indication



Overview



The Wi-Fyre Wireless A2R Heat Detector consists of a ProFyre ROR heat detector head combined with the Wi-Fyre wireless base. The ROR heat detector uses a thermistor arrangement to sense a quick rise in temperature and also a final threshold temperature of 57°C.



Approvals

All Wi-Fyre Devices are fully certified to EN54-25 - the European product standard for wireless fire alarms, which necessitates third party assessment to confirm that it meets very specific requirements.

Wi-Fyre also complies with ENTSI 300:200 - the standard requirements for the Radio Equipment Directive (RED), and BS 5839-1 - the code of practise for design, installation, commissioning and maintenance of fire alarm systems in non-domestic premises.



CE 16
1008

EF-109-DoP-1

1008-CPR-MC 69251485
0001






Tech Specs

Radio

 Operating Frequency	868 - 870 MHz, 14dBm
 Range	150m open area

Detection

 Detector Class	Rate of rise & fixed heat
 Alarm Condition	Rate of rise or fixed heat trigger @ 57°C
 Coverage	50m ²

Electrical

 Power Source







4 x Lithium AA Cell (Soft LS14500)

 Battery Life

Up to 3 years

Environmental

 Operating Temperature	-10 to +50°C
 Humidity	93% rH (non-condensing)
 Ingress Protection	IP21
 Design Environment	Indoor use only

Mechanical

 Housing Material

Polycarbonate and ABS

 Colour



White



Tech Specs

Size & Weight

Size



Weight

0.30kg (0.66 lbs)

Ordering Information

Part Code	Description
10-011	Wireless A2R (ROR) Heat Detector with Batteries
10-080	Wireless Detector Lithium Metal Battery Pack
10-084	Wireless Detector Base without Batteries
10-086	Wireless A2R (ROR) Detector Head