

IP Network PA Amplifier (60W)

IP-8060AMP

Features:

- ✓ The head of IP network audio system.
- ✓ Ideal solution for small size multiple room network audio system like school, office and hospital.
- ✓ Built-in IP network audio adapter and PA 60W digital Class-D power amplifier in 1U.
- ✓ Multiple music programs could be matrix distributed from server to different zones.
- ✓ Built-up over existing LAN/WAN network system, non-dedicated network system is needed.
- ✓ Start time is less than 1 second.
- ✓ Design with 3" colorful LCD in English display.
- ✓ 3 mic inputs, 2 aux inputs and 1 line output.
- ✓ With 100V speaker outputs by screw terminal.
- ✓ Mic1 input on front panel with VOX priority.
- ✓ Separate volume and tone control for each 5 inputs.
- ✓ The output priority level from sources, network program are editable.
- ✓ With short circuit contact output for relay or communication with third party system.
- ✓ Support LAN/WAN, Ethernet system, support over gateway and over router.



Specifications:

Model	IP-8060AMP
Description	IP Network PA Amplifier
Rated Power Output	60W
Power Supply	AC230V or 115V, 50-60Hz
Power Consumption	80W
Network Protocol	TCP, UDP, ARP, ICMP, IGMP
Network Chip Speed	10/100Mbps
Audio Format	Mp2/Mp3/PCM/ADPCM
Screen Display	3" colorful LCD English, 128×64 resolution
Audio Sampling	8KHz-44.1kHz, 16bits, 8Kbps-32Kbps
Speaker Output	100V speaker output by screw terminal
S/N Ratio	>90dB
Frequency Response	20-20KHz
Data Delay	<100ms
Connector	3 Mic input, 2 aux input, 1 line output, 100V speaker outputs, one contact output
Dimension & Weight	483(W)×256(D)×44mm(H), 9.8kg

Rear Panel:

